

## Product Information Sheet

# DE-SCALE XP

*A fast-acting and effective product for the removal of cement and mortar splashes, efflorescence, lime-scale and rusty marks from a wide variety of building surfaces.*

*DE-SCALE XP has a powerful dissolving action that handles deposits other products cannot touch but, at the same time, is totally free from the fuming behaviour that makes other products a nuisance to work with.*

*Versatile and useful DE-SCALE XP is ideal for use by builders, plumbers, renovators and the engineering trades generally for removal of cement from tools & equipment, efflorescence & excess mortar from brickwork & masonry and limescale from pipework etc.*

### FEATURES

### BENEFITS

<i>Non-fuming</i>	<i>makes mortar, cement dust and efflorescence removal both safer and much more pleasant an operation.</i>
<i>Fast-acting</i>	<i>removes mortar, cement scale, efflorescence and rusty stains even as you watch.</i>
<i>Effective</i>	<i>will dissolve many times its own weight of scale and deposits – lifts deposits that other products cannot handle.</i>
<i>Biodegradable</i>	<i>will not add to the environmental burden when carrying out these very necessary and important tasks</i>

## Application and Safety Information

### DE-SCALE XP

**Description:** Selected aqueous mineral acids, combined with special surface wetting agents, which ensure rapid and even action on surfaces, with special inhibitors which ensure the protection of iron and steel parts as cement, scale and rust are rapidly removed.

**Application:** Depending on the heaviness of the deposits, the product may be used neat or diluted with up to 20 parts of water. For the removal of cement, etc., from equipment and other metal parts, apply by brush, by immersion or by circulation. Use until no more scale will dissolve then rinse well with plenty of water. For efflorescence and mortar splash removal from building surfaces, especially brickwork, a special procedure is required to prevent product being drawn too far into the masonry, etc., by capillary action; Firstly, thoroughly wet the surface with plenty of water. Apply the product and scrub, then rinse quickly. Repeat until all deposits are gone. DO NOT let the surface dry out at any stage until finally well rinsed.

**Packaging:** Available in 210 litre or 30 litre UN-rated poly-drums and in cases of 4 x 5 litre UN-rated poly-cans.

**Physical Data:** Appearance: Clear, bright red, mobile liquid. Totally miscible with water in all proportions.  
Relative Density: about 1.15 @ 20°C  
pH: (1+5 mix) <1

#### Emergency Action On:

**Skin Contact** Rinse off with water

**Eye Contact:** Flush out with plenty of water.

**Ingestion:** Drink plenty of water and seek medical attention. DO NOT try to induce vomiting.

**Spillage:** Absorb in granules, sweep up, bag and bin.

#### Other Information:

For full Health and Safety information, ask for;  
Sheet Ref.: HS-De-Scale XP

Sheet Ref: PL-DD21 /02

Date of Issue: 26/02/2010